

WHAT IS CLAIMED IS:

1. A code reader to read a code from a data recording medium which records data as an optically readable code and is provided with a non-interference area around said code to prevent presence of only an interference image having an attribute causing an error during reading of said code, said code reader comprising:

an image pickup section to pick up said code;

a guide section configured to specify positional relationship between said image pickup section and said code;

a code detection section to set a code detection area in an image pickup screen obtained in said image pickup section and detect at least part of said code from the inside thereof; and

a restoration section to specify said code from said image pickup screen based on a detection position of at least part of said code detected in said code detection section and restore data recorded in said code, wherein

said code detection area is determined based on an alignment error between said image pickup section and said code due to said guide section and a specification of said code.

2. The apparatus according to claim 1, wherein said guide section allows part thereof as a guide

positioning section to touch a recording medium
positioning section as part of said recording medium
and determines a positional relationship between said
image pickup section and the code.

5 3. The apparatus according to claim 2, wherein
said guide section is a slit, and
said data recording medium is shaped into a card,
and inserting said card-shaped data recording medium
into said slit determines positional relationship
10 between said image pickup section and the code.

4. The apparatus according to claim 2, wherein
said alignment error is determined by a contact
error between a guide section and a recording medium in
said guide positioning section.

15 5. The apparatus according to claim 2, wherein
said alignment error is determined by an assembly
error of said image pickup section against said guide
positioning section.

20 6. The apparatus according to claim 2, wherein
said alignment error is determined by a recording
position error of said code against said recording
medium positioning section.

25 7. The apparatus according to claim 1, wherein
said non-interference area is widened on one of
upper side and lower side of said code, and
said code detection section starts detection from
the wider side of said non-interference area and

10086124.02003

8. The apparatus according to claim 1, wherein
said code comprises a plurality of blocks,
each of said blocks comprises an arrangement of
5 a data area containing data divided from said data,
a marker area containing a marker for identifying that
block, and a block ID area containing block ID
information for independently identifying that block,
according to a specified positional relationship,

said restoration section specifies said code from
said image pickup screen in units of blocks and
restores said divided data.

20 said non-interference area is narrowed in a
portion other than an edge used to start scanning said
code, and

25 10. A code reader to read said code from a data
recording medium which records data as an optically
readable code, comprising:

an image pickup section to pick up a code;

an image detection section to detect a specified image from an image pickup screen obtained in said image pickup section, said specified image being

5 provided near said code on a data recording medium and being positioned according to a specified positional relationship with said code; and

10 a restoration section to specify said code from said image pickup screen based on a detection position of said specified image detected in said image detection section and to restore data recorded in said code.

11. The apparatus according to claim 10, wherein said specified image is part of an adjacent code.

15 12. A data recording medium comprising:

a portion where data is recorded as an optically readable code; and

20 a non-interference area which is provided around said code and prevents presence of only an interference image having an attribute causing an error during reading of said code, wherein

25 said recording medium stores said code read by a code reader having an image pickup section to pick up a code, a code detection section to set a code detection area in an image pickup screen obtained in said image pickup section and detect part of said code from the inside thereof, a restoration section to

4005434 033092

5

10

15

15

20

20

25

25

16. The medium according to claim 13, wherein

said alignment error is determined by an assembly error of said image pickup section against said guide positioning section.

17. The medium according to claim 13, wherein

5 said alignment error is determined by a recording position error of said code against said recording medium positioning section.

18. The medium according to claim 12, wherein

10 a data recording medium is read by a code reader in which said code detection section starts detection processing from a specified position in said code detection area and terminates detection processing when detecting part of the code, and

15 said non-interference area is widened on one of upper side and lower side of said code for said code detection section to start detection.

19. The medium according to claim 12, wherein

20 said code comprises a plurality of blocks, and each of said blocks comprises an arrangement of a data area containing data divided from said data, a marker area containing a marker for identifying that block, and a block ID area containing block ID information for independently identifying that block, according to a specified positional relationship.

25 20. The medium according to claim 19, wherein

 said data recording medium is read by a code reader which reads said code by means of relative

400541-123004

scanning with reference to said image pickup section
and provides said code detection section with
a narrower code detection area used to detect
the latter part of the code than a code detection area
used to detect the beginning of the code during said
scanning, and

said non-interference area is narrowed in a
portion other than an edge used to start scanning said
code.

21. A data recording medium comprising:

a portion where data is recorded as an optically
readable code; and

the other portion, wherein

said recording medium stores said code read by
a code reader having an image pickup section to pick up
a code, an image detection section to detect
a specified image from an image pickup screen obtained
in said image pickup section, and a restoration section
to specify said code from said image pickup screen
based on a detection position of said specified image
detected in said image detection section and to restore
data recorded in said code, and

said specified image is provided near said code on
a data recording medium and is positioned according to
a specified positional relationship with said code.

22. The medium according to claim 21, wherein
said specified image is part of an adjacent code.

1005424.0000

23. A card-shaped data recording medium
comprising:

a portion which records visually readable images
such as a character, symbol, figure, pattern, photo,
5 etc.; and

a portion which records data as an optically
readable code along a given cut side, wherein

a non-interference area is provided around said
code to inhibit presence of only an interference image,
10 out of said visually readable images, having an
attribute causing an error during reading of said code,
and

said non-interference area contains a longer width
between said code and said cut side than a width
15 between said code and said visually readable image
arranged adjacently to said code.

40066424-022803